

MATERIAL SAFETY DATA SHEET

NAPALAN SOFT FEEL
PRODUCT CODE: 5503
DATE: 1/3/06
SUPERCEDES:

HAZARD RATINGS (0-4)
FIRE 2 REACTIVITY 0
TOXICITY 2 SPECIAL

SUPPLIER: Suede Products
 18600 Graphics Court Tinley Park, IL 60477
 (708) 614-0939

EMERGENCY PHONE
INFOTRAC: (800) 535-5053

TRADE NAME: NAPALAN SOFT FEEL
PRODUCT TYPE: Leather conditioner
CHEMICAL FORMULA: Mixture
CHEMICAL NAME: N/A

COMPONENT LIST - SECTION I

<u>COMPONENT</u>	<u>CAS</u>	<u>%</u>	<u>TLV</u>	<u>TLV</u>
	<u>REG#</u>		<u>OSHA</u>	<u>ACGIH</u>
Alcohol Blend	Mixture	30 - 40	200 ppm	200 ppm
Silicone	Mixture	20 - 25	N/A	N/A

This product contains no ingredients that are listed in the SARA III, Section 313 Inventory.

PHYSICAL PROPERTIES - SECTION II

APPEARANCE: Clear liquid with alcohol odor.
pH: 5.4
VISCOSITY: <10 cps
FREEZING POINT: N/D
BOILING POINT: N/D
VAPOR PRESSURE: N/D
VAPOR DENSITY: < 1
SOLUBILITY IN WATER: Substantial
VOLATILE (% WT): Approx. 95
SPECIFIC GRAVITY: 0.83
EVAPORATION RATE: < 1

FIRE AND EXPLOSION HAZARD - SECTION III

FLASH POINT: 73° F
LOWER EXPLOSION LIMIT: N/D UPPER EXPLOSION LIMIT: N/D
AUTO IGNITION TEMP: N/D
EXTINGUISHING MEDIUM: Foam, alcohol foam, CO₂, dry chemical, water spray

SPECIAL FIRE FIGHTING PROCEDURES:

Cool and use caution when approaching fire-exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Container may burst in heat of fire. Product contains water so may not support combustion.

HEALTH HAZARDS - SECTION IV

THRESHOLD LIMIT VALUES: None established.
PRIMARY ROUTES OF EXPOSURE: Eye, skin, inhalation
CARCINOGENS OR SUSPECTED CARCINOGENIC INGREDIENTS: None
EFFECTS OF OVEREXPOSURE:

IF IN EYES - Direct contact can cause irritation.

IF ON SKIN - Prolonged or repeated contact may cause irritation.

IF INHALED - Spray mist may cause irritation to nose, throat and lungs.

IF SWALLOWED - May cause nausea, vomiting and abdominal pain.

NAPALAN SOFT FEEL - PAGE 2

EMERGENCY AND FIRST AID PROCEDURES:

IF IN EYES: Immediately flush eyes with clear water for at least 15 minutes, occasionally lifting lower and upper lids. If irritation persists, seek medical attention.

IF ON SKIN: Wash with soap and water.

IF SWALLOWED: Drink large amounts of water or milk and seek medical attention. Do not give anything by mouth to an unconscious person.

IF INHALED: If mist causes discomfort, leave area and move to fresh air.

REACTIVITY - SECTION V

STABILITY: Stable

CONDITIONS TO AVOID: Unknown

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield oxides of carbon.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, bleach.

SPILLS OR LEAK PROCEDURE - SECTION VI

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate all ignition sources. Rinse area thoroughly with water.

WASTE DISPOSAL METHODS:

For undiluted product: Disposal is regulated under RCRA as ignitable waste. Waste from normal product use may be sewerred in compliance with federal, state and local regulations.

SPECIAL PROTECTION - SECTION VII

VENTILATION TYPE: General room ventilation is normally adequate.

RESPIRATORY PROTECTION: Not required under normal use conditions.

PROTECTIVE GLOVES: Impervious

EYE PROTECTION: Safety glasses if splashing likely.

OTHER PROTECTIVE EQUIPMENT:

STORAGE AND HANDLING - SECTION VIII

Keep from freezing. Do not weld, heat or drill on or near container.

SHIPPING - SECTION IX

PROPER SHIPPING NAME: Paint Related Material

U.S. DOT HAZARD CLASS: 3, UN1263, PG III

LABEL REQUIREMENTS: Flammable

MISCELLANEOUS - SECTION X

ABBREVIATIONS:	N/A: Not applicable	UNK: Unknown
	N/D: Not determined	< : Less than
	N/E: Not established	> : Greater than

PREPARED BY: JOHN ROTH