

# MATERIAL SAFETY DATA SHEET

## NAPALINE NAVY BLUE

DATE: 3/4/09  
SUPERSEDES: 1/3/06

HAZARD RATINGS (0-4)  
FIRE 2 REACTIVITY 0  
TOXICITY 2 SPECIAL

SUPPLIER: Suede Products  
18600 Graphics Court Tinley Park, IL 60477  
(708) 614-0939

EMERGENCY PHONE  
INFOTRAC: 800-535-5053

TRADE NAME: Napaline Navy Blue  
PRODUCT TYPE: Leather dye  
CHEMICAL FORMULA: Mixture  
CHEMICAL NAME: N/A

### COMPONENT LIST - SECTION I

<u>COMPONENT</u>	<u>CAS</u>		<u>TLV</u>	<u>TLV</u>
	<u>REG#</u>	<u>%</u>	<u>OSHA</u>	<u>ACGIH</u>
Alcohol Blend	MIXTURE	30 - 40	200 ppm	200 ppm
Blue Pigment Dispersion	MIXTURE	5 - 10	N/A	N/A

This product contains no ingredients that are listed in the SARA III, Section 313 Inventory.

### PHYSICAL PROPERTIES - SECTION II

APPEARANCE: Aqueous blue liquid with solvent odor  
pH: N/D  
VISCOSITY: <10 cps  
FREEZING POINT: N/D  
BOILING POINT: N/D  
VAPOR PRESSURE: N/D  
VAPOR DENSITY: < 1  
SOLUBILITY IN WATER: Substantial  
VOLATILE (% WT): Approx. 95  
SPECIFIC GRAVITY: 0.91  
EVAPORATION RATE: < 1

### FIRE AND EXPLOSION HAZARD - SECTION III

FLASH POINT: 76° F  
LOWER EXPLOSION LIMIT: N/D UPPER EXPLOSION LIMIT: N/D  
AUTO IGNITION TEMP: N/D  
EXTINGUISHING MEDIUM: Foam, alcohol foam, CO<sub>2</sub>, dry chemical, water spray  
SPECIAL FIRE FIGHTING PROCEDURES:

Cool and use caution when approaching fire-exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Container may burst in heat of fire. Product contains water so may not support combustion.

### HEALTH HAZARDS - SECTION IV

THRESHOLD LIMIT VALUES: None established.  
PRIMARY ROUTES OF EXPOSURE: Eye, skin, inhalation  
CARCINOGENS OR SUSPECTED CARCINOGENIC INGREDIENTS: None  
EFFECTS OF OVEREXPOSURE:

- IF IN EYES - Direct contact can cause irritation.
- IF ON SKIN - Prolonged or repeated contact may cause irritation.
- IF INHALED - Spray mist may cause irritation to nose, throat and lungs.
- IF SWALLOWED - May cause nausea, vomiting and abdominal pain.

## NAPALINE NAVY BLUE - PAGE 2

### EMERGENCY AND FIRST AID PROCEDURES:

IF IN EYES: Immediately flush eyes with clear water for at least 15 minutes, occasionally lifting lower and upper lids. If irritation persists, seek medical attention.

IF ON SKIN: Wash with soap and water.

IF SWALLOWED: Drink large amounts of water or milk and seek medical attention. Do not give anything by mouth to an unconscious person.

IF INHALED: If mist causes discomfort, leave area and move to fresh air.

---

### REACTIVITY - SECTION V

STABILITY: Stable

CONDITIONS TO AVOID: Unknown

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield oxides of carbon.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, bleach.

---

### SPILLS OR LEAK PROCEDURE - SECTION VI

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate all ignition sources. Rinse area thoroughly with water.

#### WASTE DISPOSAL METHODS:

For undiluted product: Disposal is regulated under RCRA as Ignitable Waste. Waste from normal product use may be sewerred in compliance with federal, state and local regulations.

---

### SPECIAL PROTECTION - SECTION VII

VENTILATION TYPE: General room ventilation is normally adequate.

RESPIRATORY PROTECTION: Not required under normal use conditions.

PROTECTIVE GLOVES: Impervious.

EYE PROTECTION: Safety glasses if splashing likely.

OTHER PROTECTIVE EQUIPMENT:

---

### STORAGE AND HANDLING - SECTION VIII

Keep from freezing. Do not weld, heat or drill on or near container.

---

### SHIPPING - SECTION IX

PROPER SHIPPING NAME: Paint Related Material

U.S. DOT HAZARD CLASS: 3, UN1263, PG III

LABEL REQUIREMENTS: Flammable

---

### MISCELLANEOUS - SECTION X

ABBREVIATIONS:	N/A: Not applicable	UNK: Unknown
	N/D: Not determined	< : Less than
	N/E: Not established	> : Greater than

PREPARED BY: JOHN ROTH