

# MATERIAL SAFETY DATA SHEET

## LEATHER FINISH NAVY BLUE W-3000

PRODUCT CODE: 5370  
DATE: 1/3/06  
SUPERCEDES:

HAZARD RATINGS (0-4)  
FIRE 0 REACTIVITY 0  
TOXICITY 1 SPECIAL

SUPPLIER: Suede Products  
18600 Graphics Court Tinley Park, IL 60477  
(708) 614-0939

TRADE NAME: Leather Finish Navy Blue W-3000  
PRODUCT TYPE: Leather dye  
CHEMICAL FORMULA: Mixture  
CHEMICAL NAME: N/A

### COMPONENT LIST - SECTION I

<u>COMPONENT</u>	<u>CAS</u>	<u>REG#</u>	<u>%</u>	<u>TLV</u>	<u>OSHA</u>	<u>TLV</u>	<u>ACGIH</u>
1-Methyl -2-Pyrrolidone	872-50-4		2 - 5	N/E		N/E	

This product contains no ingredients that are listed in the SARA III, Section 313 Inventory.

### PHYSICAL PROPERTIES - SECTION II

APPEARANCE: Aqueous dark blue liquid with slight odor  
pH: N/D  
VISCOSITY: <10 cps  
FREEZING POINT: 32° F  
BOILING POINT: 212° F  
VAPOR PRESSURE: N/D  
VAPOR DENSITY: < 1  
SOLUBILITY IN WATER: Complete  
VOLATILE (% WT): > 95  
SPECIFIC GRAVITY: 1.09  
EVAPORATION RATE: < 1

### FIRE AND EXPLOSION HAZARD - SECTION III

FLASH POINT: None  
LOWER EXPLOSION LIMIT: N/D UPPER EXPLOSION LIMIT: N/D  
AUTO IGNITION TEMP: N/D  
EXTINGUISHING MEDIUM: Foam, alcohol foam, CO<sub>2</sub>, dry chemical, water spray.  
SPECIAL FIRE FIGHTING PROCEDURES:

Cool and use caution when approaching fire-exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Container may burst in heat of fire. Product contains water so will not support combustion.

### HEALTH HAZARDS - SECTION IV

THRESHOLD LIMIT VALUES: None established.  
PRIMARY ROUTES OF EXPOSURE: Eye, skin, inhalation  
CARCINOGENS OR SUSPECTED CARCINOGENIC INGREDIENTS: None  
EFFECTS OF OVEREXPOSURE:

IF IN EYES - Direct contact may cause irritation.

IF ON SKIN -Prolonged or repeated contact may cause irritaion.

IF INHALED - Spray mist may cuse irritation to nose, throat and lungs.

IF SWALLOWED - May cause nausea, vomiting and abdominal pain.

**LEATHER FINISH NAVY BLUE W-3000 - PAGE 2**

**EMERGENCY AND FIRST AID PROCEDURES:**

IF IN EYES: Immediately flush eyes with clear water for at least 15 minutes, occasionally lifting lower and upper lids. If irritation persists, seek medical attention.

IF ON SKIN: Wash with soap and water.

IF SWALLOWED: Drink large amounts of water or milk and seek medical attention. Do not give anything by mouth to an unconscious person.

IF INHALED: If mist causes discomfort, leave area and move to fresh air.

---

**REACTIVITY - SECTION V**

STABILITY: Stable

CONDITIONS TO AVOID: Unknown

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield oxides of carbon.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, bleach.

---

**SPILLS OR LEAK PROCEDURE - SECTION VI**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate all ignition sources. Rinse area thoroughly with water.

WASTE DISPOSAL METHODS:

FOR UNDILUTED PRODUCT: Disposal is regulated under RCRA as ignitable waste. Waste from normal product use may be sewered in compliance with federal, state and local regulations.

---

**SPECIAL PROTECTION - SECTION VII**

VENTILATION TYPE: General room ventilation is normally adequate.

RESPIRATORY PROTECTION: Not required under normal use conditions.

PROTECTIVE GLOVES: Impervious.

EYE PROTECTION: Safety glasses if splashing likely.

OTHER PROTECTIVE EQUIPMENT:

---

**STORAGE AND HANDLING - SECTION VIII**

Keep from freezing.

**SHIPPING - SECTION IX**

PROPER SHIPPING NAME: Paints, stains or varnishes, NOI

U.S. DOT HAZARD CLASS: None

LABEL REQUIREMENTS: None

---

**MISCELLANEOUS - SECTION X**

ABBREVIATIONS:	N/A: Not applicable	UNK: Unknown
	N/D: Not determined	< : Less than
	N/E: Not established	> : Greater than

PREPARED BY: JOHN ROTH