

MATERIAL SAFETY DATA SHEET

SUPER DYE PINK

DATE: 3/9/09
SUPERSEDES: 11/20/06

HAZARD RATINGS (0-4)
FIRE 3 REACTIVITY 0
TOXICITY 2 SPECIAL

SUPPLIER: Suede Products
18600 Graphics Court Tinley Park IL 60477
(708) 614-0939

EMERGENCY PHONE
INFOTRAC: (800) 535-5053

TRADE NAME: Super Dye Pink
PRODUCT TYPE: Leather dye
CHEMICAL FORMULA: Mixture
CHEMICAL NAME: N/A

COMPONENT LIST - SECTION I

<u>COMPONENT</u>	<u>CAS</u>		<u>TLV</u>	<u>TLV</u>
	<u>REG#</u>	<u>%</u>	<u>TWA</u>	<u>ACGIH</u>
Ethyl Alcohol (3)	64-17-5	5 - 10	1000 ppm	N/D
Basic Violet 10 (1,2,4)	81-88-9	1 - 5	N/A	N/A

1 - Subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right To Know Act of 1996 and of 40 CRF 372.
2 - WHMIS requires disclosure when present in a mixture above 1%.
3 - WHMIS requires disclosure when present in a mixture above 0.1%.
4 - California's Proposition 65 requires listing chemicals known to cause cancer or reproductive toxicity.

PHYSICAL PROPERTIES - SECTION II

APPEARANCE: Opaque pink liquid with sweet odor
FREEZING POINT: N/D
INITIAL BOILING POINT: 173° F (78.3 C) (ethanol)
VAPOR PRESSURE: N/A
VAPOR DENSITY (AIR = 1.0): > 1
SOLUBILITY IN WATER: Miscible
VOLATILE (% WT): Approx. 95
SPECIFIC GRAVITY: 0.99
EVAPORATION RATE(ETHER = 1.0): > 1
% VOC BY WT: < 47

FIRE AND EXPLOSION HAZARD - SECTION III

FLASH POINT: 50° F (10 C) by TCC (ethanol) (SETA test @ WC = 65° F)
LOWER EXPLOSION LIMIT: N/D UPPER EXPLOSION LIMIT: N/D
AUTO IGNITION TEMP: N/D
EXTINGUISHING MEDIUM: Foam, CO₂, dry chemical
SPECIAL FIRE FIGHTING PROCEDURES:

Water may be used to cool unruptured containers to prevent pressure buildup and possible auto-ignition or explosion when exposed to extreme heat. Use full protective equipment, including self-contained breathing apparatus, to protect firefighters from any hazardous combustion products.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Keep containers tightly closed. Isolate from heat, sparks, electrical equipment and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

HEALTH HAZARDS - SECTION IV

This product has not been tested as a whole. The acute and/or chronic hazards listed have been drawn from the information on the ingredient MSDS.

PERMISSIBLE CONCENTRATIONS (AIR): See Section I for ingredient levels.

PRIMARY ROUTES OF EXPOSURE: Skin, inhalation

EFFECTS OF OVEREXPOSURE:

(Short Term): Eye and respiratory tract irritation and possible drowsiness above 1000 ppm exposure. Prolonged high concentration exposures may cause headaches, tremors, and fatigue.

(Long Term): Effects of long term exposure to controlled concentrations have not been determined.

EMERGENCY AND FIRST AID PROCEDURES:

EYE AND SKIN CONTACT: Caution! Can cause eye and skin irritation. Protect eyes, skin and clothing from contact with product. Wear recommended protective equipment. Wash thoroughly after handling. In case of eye or skin contact, immediately flush with plenty of water. Wash skin with soap and water. Get medical attention if irritation persists.

IF SWALLOWED: Caution! May be harmful if swallowed. Wash thoroughly after handling. Consult physician or Poison Control Center immediately.

IF INHALED: Caution! May be harmful if inhaled. Do not inhale product. Keep container closed. Use only with adequate ventilation. If inhaled, immediately move to fresh air. If breathing is difficult, give oxygen. Call a physician.

REACTIVITY - SECTION V

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Extreme heat; contact with oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

INCOMPATIBILITY (MATERIALS TO AVOID): Keep away from oxidizing materials such as hydrogen peroxide, nitric acid, acetyl chloride.

SPILLS OR LEAK PROCEDURE - SECTION VI

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove ignition sources. Add dry material to absorb spill (if large spill, dike to contain). Using recommended protective and explosion-proof equipment, pick up and containerize for recovery or waste disposal. Flush area with water, collect for disposal or sewer if allowed.

WASTE DISPOSAL METHODS:

This product, if disposed as shipped, meets EPA criteria of a hazardous waste as specified in 40 CFR 261 on the basis of its ignitability.

SPECIAL PROTECTION - SECTION VII

VENTILATION TYPE: Use only in approved spray booth with adequate exhaust (see OSHA 29 CFR 1910.107).

RESPIRATORY PROTECTION: Use NIOSH/MSHA approved combined particle and vapor respirator if local exhaust is inadequate to maintain air contamination below TLVs (SEE 29 CFR 1910.134).

PROTECTIVE GLOVES: Use impervious gloves to prevent prolonged or repeated contact with skin (see 29 CFR 1910.132).

EYE PROTECTION: Safety glasses with sideguards, chemical goggles or face shield.

OTHER PROTECTIVE EQUIPMENT: Use full sleeve clothing, aprons, impervious boots or shoes to prevent skin contact.

HYGIENIC PRACTICES: Wash hands before eating or using the washroom. Smoke in approved smoking areas only.

STORAGE AND HANDLING - SECTION VIII

Do not store in high temperature areas or near fire or open flame sources. For proper storage conditions see OSHA 29 CFR 1910.106. Do not take internally. Avoid prolonged contact with skin. Ground and bond containers when transferring to avoid static charge buildup.

SHIPPING - SECTION IX

PROPER SHIPPING NAME: Paint Related Material

U.S. DOT HAZARD CLASS: 3, UN1263, PG II

LABEL REQUIREMENTS: Flammable

MISCELLANEOUS - SECTION X

ABBREVIATIONS:	N/A: Not applicable	UNK: Unknown
	N/D: Not determined	< : Less than
	N/E: Not established	> : Greater than

It is the user's responsibility to provide a safe workplace and user may refer to this data sheet and other available information in drafting health and safety guidelines for employees and customers who use this product, or materials made with this product. User is solely responsible for handling this product or wastes containing this product, in a safe manner and in compliance with all applicable federal, state and local laws and regulations. User assumes the risk in its use of this product.

As the conditions or methods of using this product are beyond vendor's control, vendor expressly disclaims any liability for any use of this product.

PREPARED BY: JOHN ROTH

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied, is made with respect to the information contained herein. This material safety data sheet was prepared to comply with the OSHA Hazard Communication Standard (29 CFR 1910.1200).